

# Defining Login Session Options

You can perform different tasks when redirecting a user to Yellowfin, such as suppressing the header, navigating to a particular report, displaying a particular dashboard, etc. This is done by defining user session options in the login token.

Session options can be passed in two ways:

1. As part of a URL
2. As part of a SSO call

## Passing Session Options via URL

Pass session options through a URL. For example:

```
http://<yellowfin-server>/logon.i4?  
LoginWebserviceId=<token>&disableheader=true&entry=TIMELINE
```

With the inclusion of `entry=TIMELINE`, and `disableheader` options in the URL, the user will be taken to the Timeline page, and the Yellowfin header will be disabled, when they log in.

## Passing Session Options as Part of a SSO Call

A Single Sign-On, or SSO, call (which includes `LOGINUSER` and `LOGINUSERNOPASSWORD`) can be used to pass sessions, by applying the `setParameters()` method.

For example:

```
String[] parameters = new String[] { "ENTRY=TIMELINE", "DISABLEHEADER=TRUE" };  
  
rsr.setParameters(parameters);
```

Similarly, this example will disable the Yellowfin header, and the user will be redirected to the Timeline page.

## Available Session Options

Below is a list of key session options and their descriptions that you can use to pass through URLs or the Parameters method:

Parameter Key	URL Key	Description
YFTOOLBAR	yftoolbar	TRUE/FALSE. To hide the Yellowfin toolbar for this session.

ENTRY	entry	<p>Determine the user's only entry point on completion of the login process. This is used in conjunction with other parameters to determine the content the user is shown. Possible values include:</p> <ul style="list-style-type: none"> <li>• DASHBOARD</li> <li>• REPORTLIST</li> <li>• BROWSE</li> <li>• BROWSETAB</li> <li>• CREATEREPORT</li> <li>• EDITREPORT</li> <li>• VIEWREPORT</li> <li>• ADMINISTRATION</li> <li>• EDITDASHBOARD</li> <li>• VIEWDASHBOARD</li> <li>• VIEWSTORYBOARD</li> <li>• TIMELINE</li> </ul>
REPORTID	reportid	Used with ENTRY = EDITREPORT or VIEWREPORT. This is the internal ID of the report to redirect to.
REPORTUUID	reportuuid	Used with ENTRY = EDITREPORT or VIEWREPORT. This is the UUID of the report to redirect to.
STORYBOARDUUID	storyboarduuid	Used with ENTRY = VIEWSTORYBOARD. This is the UUID of the storyboard to redirect to.
MOBILEDEVICE	mobiledevice	TRUE/FALSE. Takes the user to a mobile version of the Yellowfin interface.
REPORTNAME	reportname	Used with ENTRY = EDITREPORT or VIEWREPORT. This is the name of the report to redirect to.
DISABLESOURCEFILTERS		TRUE/FALSE. Disables Source Filter or Client Reference Filters for this user, for this session. This allows the user to see all the data. This doesn't work for content based on Client Source Substitution.
DISABLEHEADER	disableheader	TRUE/FALSE. Hides the Yellowfin header for this session.
HIDEHEADER	hideheader	Same as DISABLEHEADER.
DISABLEFOOTER	disablefooter	TRUE/FALSE. Hides the Yellowfin footer for this session.
HIDEFOOTER	hidefooter	Same as DISABLEFOOTER.
DISABLESIDENAV	disablesidenav	TRUE/FALSE. Hides the Yellowfin side navigation for this session.
HIDESIDENAV	hidesidenav	Same as DISABLESIDENAV.
DISABLELOGOFF	disablelogoff	TRUE/FALSE. Hides the Yellowfin logoff link for this session.
HIDELOGOFF	hidelogoff	Same as DISABLELOGOFF.
REASONCODE	reasoncode	Custom string (80 ASCII characters) that will be dropped in all events generated by this session. Events are dropped in the Event table in the Yellowfin database. This option can also be used with the JavaScript API.

REASONDESCRIPTION	reasondescription	Custom string (2048 ASCII characters) that will be dropped in all events generated by this session. Events are dropped in the Event table in the Yellowfin database. This option can also be used with the JavaScript API.
DASHBOARDID	dashboardid	Used with ENTRY = EDITDASHBOARD or VIEWDASHBOARD. This is the internal ID of the dashboard tab to redirect to.
DASHBOARDUUID	dashboarduuid	Used with ENTRY = EDITDASHBOARD or VIEWDASHBOARD. This is the UUID of the dashboard tab to redirect to.
FILTER<ID>	filter<ID>	Used with ENTRY = VIEWREPORT. Overrides filter values for the given report. FILTER is appended with the internal ID of the filter, plus the string representation of the filter value. For example: FILTER2134=MALE You can pass multiple filters for the one report.
SOURCEFILTER_<FILTERCODE>		Overrides the source filter values for this user, for this session. SOURCEFILTER_ is appended with the Filter Type Code from the Source Filter setup page, plus the value you wish to give access to. For example: SOURCEFILTER_COUNTRY=AU You can pass multiple source filter values for the one session. This option can also be used with the JavaScript API.
CONTENT_<INCLUDE/EXCLUDE>		<p>Overrides the content access that a user has for this session.</p> <p>CONTENT_ is appended with either INCLUDE or EXCLUDE. The value for this key is either the Content Category Code, or the Content Category UUID.</p> <ul style="list-style-type: none"> <li>• If you choose to INCLUDE content, then these will be the only Content Categories that the user will have access to.</li> <li>• If you choose to EXCLUDE content, then these excluded Content Categories will be removed from the content that the user normally has access to.</li> </ul> <p>Content Inclusion and Exclusion is based on the Category level. All sub categories with the specified category are included or excluded.</p> <p>An example of including/excluding with category codes and UUIDs: CONTENT_INCLUDE=TUTORIAL CONTENT_INCLUDE=c83357db-8aef-4ec7-ab72-fce34de9ee77 CONTENT_EXCLUDE=TUTORIAL CONTENT_EXCLUDE=c83357db-8aef-4ec7-ab72-fce34de9ee77 It is not logical to use both INCLUDE and EXCLUDE for the same session. This option can also be used with the JavaScript API.</p>

LANGUAGE=<LANGUAGE\_CODE>

Not applicable

Overrides the language of the user's session with the one specified in this parameter. Note that doing so will invalidate the default language or any translation settings configured in the browser.

For example, passing LANGUAGE=JA will force the session's language to be Japanese.