

Implementing a Custom Formatter

A custom formatter is an implementation of the class `com.hof.mi.interfaces.CustomFormatter`. The following functions must be implemented in this class:

- `public abstract String getName();`
- `public abstract boolean acceptsNativeType(int type);`
- `public abstract String render(Object value, int renderType) throws Exception;`

These methods can be overwritten, if required:

- `public boolean returnsHtml() { return false; }`
- `public boolean compareConditionalAgainstFormattedValue() { return false; }`

Function Definitions

`public abstract String getName();`

This method returns a custom formatter name as a String. This is the name that is displayed to the user when choosing a formatter. For example:

```
public String getName() {  
    return "My Formatter";  
}
```

`public abstract boolean acceptsNativeType(int type);`

This method returns true if the formatter will support fields of the given data type. Otherwise it returns false. A list of supported types is provided in the [appendix](#).

Example 1:

```
public boolean acceptsNativeType(int type) {  
  
    //accept text and numeric data  
    if (type == TYPE_TEXT  
        || type == TYPE_NUMERIC) {  
  
        return true;  
    } else {  
  
        //don't allow any other types  
        return false;  
  
    }  
}
```

Example 2:

```
public boolean acceptsNativeType(int type) {  
  
    // we can handle any type  
    return true;  
}
```

public abstract String render(Object value, int renderType) throws Exception;

This method renders a single value. The renderType argument determines which output type you are rendering for. Yellowfin executes this function for every value of the formatted column. The renderType parameter gives you a hint as to how to display the value. When outputting to document formats such as PDF/XLS, the RENDER_TEXT type is used. For a list of possible renderType values, refer to the [appendix](#).

```
public String render(Object value, int renderType) throws Exception {  
    if (value == null) return null  
    if (renderType == RENDER_LINK)  
        // Render the value for a drill-through link.  
        // In this case you almost always want to return a generic  
        // representation of the value.  
  
    return value.toString();  
}  
  
// Return the formatted value  
return "Value: " + value.toString();  
}
```

public boolean returnsHtml();

This will return true if the values returned by the formatter include HTML, but false otherwise. By default this function returns false.

public boolean compareConditionalAgainstFormattedValue();

This function returns true if the fields using this formatter should compare conditional formats against the formatted values, otherwise it returns false. By default this function returns false.

Previous topic: [Formatter prerequisites](#)

Next topic: [Embedded HTML inclusion](#)